


... for more than 40 years +

KRASO[®]

SIMPLE + TIGHT

All rights to the drawings and designs are the property of KRASO GmbH & Co. KG. •
Copying and distribution of the drawings as well as any other use require our written consent. •



KRASO[®] Wall Collar Lightning Protection Duo

Installation instructions



KRASO GMBH & CO. KG
Baumannweg 1 | DE-46414 Rhede
T +49 (0) 28 72 - 95 35 - 0
info@kraso.de | **KRASO.de**

5.9-MA.EN-v1.0-05.25-RSc.DK



KRASO® Wall Collar Lightning Protection Duo

For the water pressure tight integration of earthing cables with factory-sealed openings: square earthing strap (30 x 3.5 mm) and earthing wire (ø 8 – 10 mm)

| DafStB waterproof concrete guideline: stress class 1 + 2

Installation situation: **KRASO® Wall Collar Lightning Protection Duo with earthing strap**

1. Cut the opening of the **KRASO® Wall Collar Lightning Protection Duo** to matching the earthing strap or earthing wire.
2. Pull the **KRASO® Wall Collar Lightning Protection Duo** over the earthing strap or earthing wire.
3. Position the **KRASO® Wall Collar Lightning Protection Duo** in the centre of the base plate. Tighten the upper strap with the Torque Control Wrench **KRASO® DKS**. As soon as you hear and feel the **KRASO® DKS** break off, the ideal torque has been reached (see detailed picture).
4. Tighten the lower strap with the Torque Control Wrench **KRASO® DKS**. As soon as you hear and feel the **KRASO® DKS** break off, the ideal torque has been reached (see detailed picture).
5. Insert support cages and upper reinforcement. TEUF = top edge unfinished floor
6. Concrete the base plate.

