



KRASO® BKP Gas Installation Kits **LG 5**

for anti-twist and tear-off protection of gas utility connections, according to DVGW VP 601, incl. primary and secondary sealing elements, gas end plug, lubricant and self-cutting screws



Item	KRASO® BKP Gas Installation Kit			
Gas utility connection	Schuck DN 25	RMA DN 25*	Voigt DN 25	Voigt DN 32
KRASO® BKP Gas Installation Kit	64 €	64 €	64 €	171 €

* For rigid and flexible designs

Scope of supply: KRASO® BKP Gas Installation Kit



KRASO® BKP - Extension Sets **LG 5**

for the extension of the casing pipes for water, electricity and telecommunication in **KRASO® Builder's Convenience Boxes** with a cable protection hose provided on-site

Item	KRASO® BKP - Extension Sets				
System KRASO® BKP - floor - SET	1-fold	2-fold	3-fold	4-fold	5-fold
KRASO® BKP - floor - SET - Extension Set	29 €	56 €	81 €	108 €	135 €
KRASO® BKP - wall - Extension Set	20 €				
KRASO® BKP - wall - NFE - Extension Set	104 €				

Scope of supply:

KRASO® BKP - floor - SET - Extension Set per system including 1 x hose connection 90 and 2 x shrink hose (DN 90 to DN 75) DN 75

KRASO® BKP - wall - Extension Set including 4 x double sleeve DN 75, 8 x sealing ring, lubricant

KRASO® BKP - wall - NFE - Extension Set including 6 x heat-shrink hose 95/25, 3 x adapter pipe DN 75



spiral made of rigid PVC



compression resistance



KRASO® FLS 90 - Flexible Empty Pipe System **LG 4**

flexible empty pipe system as a cable protective hose for the extension of the **KRASO® Builder's Convenience Box - floor - SET** using the **KRASO® BKP - Extension Set**, with a smooth interior for easy cable pulling, smooth exterior for optimal sealing, flexible, increased pressure and vacuum resistance, high axial resistance, resistant to alkalis and acids, resistant to brine and sea water, good UV and ozone resistance, gas-tight and liquid-tight, RoHS-compliant (Restriction of Hazardous Substances), compression resistance 629 N, tests in line with DIN EN 61386-24 lead to the following classifications: type 250 - impact resistance: normal - classification code: N250

Item	KRASO® FLS 90
InternalDiameter ID in mm	80
External diameter in mm	88
Bending radius in mm	200
Weight in kg/m approx.	1.5
Material thickness in mm	4
Compression resistance	629 N
Classification according to DIN EN 61386-24	N250 (reached test force F: 364 N)
Stock length in m	30
KRASO® FLS 90	23 € per metre
Cutting costs*	17 €

* Without discount