



KRASO® Basement Drain

For a dry basement

- + **KRASO® Basement Drain** with integrated, removable backwater and odour stopper!
- + For the connection of up to 3 intake pipes
- + Drainage capacity: 1.8 l per second!
- + With height-adjustable and rotatable insert frame from 30 to 60 mm
- + Either with plastic or stainless steel grate
- + With water pressure tight surrounding, thermally welded **KRASO® 4 Seal**: water pressure tight up to 10 bar!
- + Also available for KG 2000: made of polypropylene (PP), mineral-filled, smooth walls, long-lasting
- + DafStB waterproof concrete guideline: stress class 1 + 2, with foil flange DIN 18533 W1-E

KRASO® Basement Drain **LG1**

for the installation in areas without traffic and for the connection of up to 3 intake pipes. Also available with **KRASO® Foil Flange**, oil- and bitumen resistant (d = approx. 50 cm). For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DafStB waterproof concrete guideline: stress class 1 + 2, with foil flange DIN 18533 W1-E

Type / Item	KRASO® Basement Drain with plastic grate	KRASO® Basement Drain with stainless steel grate
Drainage capacity	1.8 l/s	
Height	drain approx. 250 mm	
Insert frame	steplessly rotatable and height-adjustable from 30 - 60 mm	
Slot grate	class K3, 20 x 20 cm, plastic (black)	class K3, 20 x 20 cm, stainless steel
Connection	3 intake pipes: 2 x DN 50, 1 x DN 70, either for KG, HT or KG 2000 pipes	
KRASO® Basement Drain	431 €	545 €
KRASO® Basement Drain with foil flange	560 €	673 €
KRASO® PU 50	22 €	

Scope of supply: **KRASO® Basement Drain** with removable backwater stopper, integrated odour stopper, sludge trap filter and insert frame (telescopically height-adjustable from 30 to 60 mm and rotatable), two intakes DN 50, one intake DN 70, all intakes and drains either for KG, HT or KG 2000 pipes, with slot grate 20 x 20 cm made of black plastic or stainless steel, class K3 • **KRASO® Basement Drain with foil flange**, with removable backwater stopper, integrated odour stopper, sludge trap filter and insert frame (telescopically height-adjustable from 30 to 60 mm and rotatable), two intakes DN 50, one intake DN 70, all intakes and drains either for KG, HT or KG 2000 pipes, with slot grate 20 x 20 cm made of black plastic or stainless steel, class K3 300 kg



KRASO® Basement Drain
with foil flange