

KRASO* Spacer 40 mm for KDS 150 single wall penetration for the enlargement of the centre distance from 210 mm to 250 mm



KRASO® Cable Penetration KDS/DFW single wall penetration LG1

cable penetration system for installation into triple walls, with gas- and water pressure tight surrounding KRASO® 2 Seal on one side and KDS closure cover, with plug-in system on one side for forming packages, for the later installation of media lines using a KRASO® System Sealing Insert (not included in the scope of supply) or for connecting empty pipe hoses using KRASO® System Cover (not included in the scope of supply). Optionally available: KRASO® Spacer 40 mm for KDS/DFW 150 single wall penetration for the enlargement of the centre distance from 210 mm to 250 mm | DafStB waterproof concrete guideline: stress class 1 + 2

Type / Item	KRASO® KDS/DFW single wall penetration													
Available standard wall thicknesses in cm	6 ¹	7	10	15	17.5	20	24	25	30	35	36.5	40	45	50
KRASO® KDS/DFW 90 single wall penetration	29 €													
KRASO® KDS/DFW 150 single wall penetration	34 €													
Surcharge per penetration: KRASO* Spacer 40 mm for KDS/DFW 150 single wall penetration							9	€						

 $^{^{\}rm 1}$ Only for KRASO* Cable Penetration KDS/DFW 90 single wall penetration

Scope of supply: KRASO® Cable Penetration KDS/DFW 90 or KDS/DFW 150 single wall penetration, KDS closure cover, KRASO® Cover as an installation aid • Optionally available: KRASO® Spacer 40 mm for KDS/DFW 150 single wall penetration, factory-assembled

Further wall thicknesses available on request!





KRASO® Cable Penetration KDS 150 single wall penetration with plug-in sleeve LG1

for later installation of cables or pipes using KRASO® System Sealing Insert KDS 150 (not included in the scope of supply) or KRASO® System Cover KDS 150 (not included in the scope of supply), with water pressure tight surrounding KRASO® 4 Seal, with plug-in system on one side for forming packages, one side with plug-in sleeve including connection for KG, HT or KG 2000 pipes DN 160 | DafStB waterproof concrete guideline: stress class 1 + 2

Type / Item	KRASO® KDS 150 single wall penetration with plug-in sleeve								
Available standard wall thicknesses in cm	20	24	25	30	35	36.5	40	45	50
KRASO® KDS 150 single wall penetration with plug-in sleeve					48 €				

Scope of supply: KRASO® Cable Penetration KDS 150 single wall penetration with plug-in sleeve, KDS 150 closure c over and KRASO® Cover as an installation aid

Further wall thicknesses available on request!





KRASO® Cable Penetration KDS 150 single wall penetration with hose connection LG1

for later installation of cables or pipes using KRASO® System Sealing Insert KDS 150 (not included in the scope of supply) or KRASO® System Cover KDS 150 (not included in the scope of supply), with water pressure tight surrounding KRASO® 4 Seal, with plug-in system on one side for forming packages, one side with hose connection e.g. for KRASO® FLS - Flexible Empty Pipe System

| DafStB waterproof concrete guideline: stress class ${f 1} + {f 2}$

Type / Item	KRASO® KDS 150 single wall penetration with hose connection					
Available standard wall thicknesses in cm	30					
KRAS0® KDS 150 single wall penetration with hose connection 110	113 €					
KRASO® KDS 150 single wall penetration with hose connection 160	117 €					

Scope of supply: KRASO® Cable Penetration KDS 150 single wall penetration with hose connection

Further wall thicknesses available on request!