

The
alternative to a
fixed-loose flange!

NEW BUILDING
REHABILITATION

1.5
bar

W1 -E
W2.1 -E

KRASO® Flange Pipes

Simple and effective integration into bituminous sealing

- + For new buildings and rehabilitation - according to DIN 18533 W1 -E and W2.1 -E
- + Simple and effective integration into bituminous sealing ("black tank"): bitumen thick coating and reactive sealing, sheeting, concrete and brick walls
- + Water pressure tight up to 1.5 bar – MPA-tested!
- + Made of dimensionally and pressure stable solid wall material with low abrasion! Installation even at lower temperatures
- + Pipe and pipe material in accordance with DIN EN 1401 (KG) or DIN EN 14758 (KG 2000)



KRASO® PU 50:
high-quality, permanently
elastic and strong PU-sealant!
(290 ml - cartridge).
Our recommendation for
all products with
KRASO® Foil Flange!



KRASO® Flange Pipe KG



KRASO® Flange Pipe for KG 2000



KRASO® Flange Pipe FE



KRASO® Type KMB



KRASO® Type KMB for KG 2000



KRASO® Type ÜSF



KRASO® Flange Pipe KG **LG 1**

for retrofit installation, for the connection to KG/HT pipes, made of high-quality, dimensionally and pressure stable solid wall material, with formed plug-in sleeve on one side and **KRASO® Foil Flange**, oil- and bitumen resistant, surrounding approx. 15 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DIN 18533 W1 -E and W2.1 -E

Type / Item	KRASO® Flange Pipe Type KG							
Diameter DN	110	125	160	200	250	315	400	500
Delivery length in cm	50							
KRASO® Flange Pipe Type KG	47 €	49 €	62 €	78 €	154 €	230 €	293 €	450 €
KRASO® PU 50	22 €							

Further diameters and lengths from 50 cm available on request!



KRASO® Flange Pipe for KG 2000 **LG 1**

for retrofit installation, for the connection to KG 2000 pipes, made of high-quality, dimensionally and pressure stable solid wall material, with formed plug-in sleeve on one side and **KRASO® Foil Flange**, oil- and bitumen resistant, surrounding approx. 15 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DIN 18533 W1 -E and W2.1 -E

Type / Item	KRASO® Flange Pipe for KG 2000							
Diameter DN	110	125	160	200	250	315	400	500
Delivery length in cm	50							
KRASO® Flange Pipe for KG 2000	62 €	79 €	87 €	122 €	279 €	389 €	499 €	652 €
KRASO® PU 50	22 €							

Further diameters and lengths from 50 cm available on request!



KRASO® Flange Pipe FE **LG 1**

thick-walled true diameter plastic casing for retrofit installation of pipes and cables using a sealing insert (not included in the scope of supply), with **KRASO® Foil Flange**, oil- and bitumen resistant, surrounding approx. 15 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. ID = InternalDiameter flange pipe FE | DIN 18533 W1 -E and W2.1 -E

Type / Item	KRASO® Flange Pipe Type FE					
InternalDiameter ID	100	125	150	200	250	300
External diameter in mm	110	140	160	210	263	314
Delivery length in cm	50					
KRASO® Flange Pipe Type FE	45 €	49 €	56 €	80 €	113 €	134 €
KRASO® PU 50	22 €					

Further diameters and lengths from 50 cm available on request!