



KRASO® Pump Sump Poly 400 LG2

for collecting waste water, with water pressure tight surrounding, thermally welded **KRASO* 4 Seal**, shear key and pipe connection DN 110, suitable for KG, HT and KG 2000 pipes | **DafStB waterproof concrete guideline: stress class 1 + 2**

Type / Item		KRASO® Poly 400 / 60	KRASO® Poly 400 / 80
Internal diameter in cm		38.2	38.2
Internal height in cm		60	80
DN 110	h1	20	20
DN 110	h2		41
Weight approx. in kg		17	21
KRASO® Pump Sump Poly 400		524 €	614 €
Surcharge: per each 10 cm additional height		47 €	
Surcharge: for change of the height of the connection		23 €	

Special sizes and designs available on request!





for collecting waste water, with water pressure tight surrounding, thermally welded **KRASO® 4 Seal**, shear key and pipe connection DN 110 suitable for KG, HT and KG 2000 pipes, water pressure tight empty pipe system with protective cover, pump sump protective cover for the shell construction phase | DafStB waterproof concrete guideline: stress class 1 + 2

Type / Item		KRASO® Poly 400 / 80 - LR	KRASO® Poly 400 / 100 - LR
Internal diameter in cm		38.2	38.2
Internal height in cm		80	100
Intake DN 110	h1	30	30
Empty pipe DN 110	h2	34	54
Installation weight approx. in kg		21	23
KRASO® Pump Sump Poly 400 - LR		841€	866 €

Scope of supply: KRASO® Pump Sump Poly 400 - LR with protective cover, pump sump protective cover for the shell construction phase Special sizes and designs available on request!

