




KRASO® Pump Sump Poly 400
- complete -
Check the installation video
(just scan the QR code!)



KRASO® Pump Sump Poly 400 - complete - pump



KRASO® Pump Sump Poly 400 - complete

Light, tight, complete

- + Light and water pressure tight complete solution for sewage free of faeces - for new buildings or rehabilitation!
- + Saves time and money: simple installation due to light weight - no additional formwork or concreting sections for several days required!
- + No higher risks occurring by leaking concrete joints and/or pipe connections!
- + DafStB waterproof concrete guideline: stress class 1 + 2



KRASO® Pump Sump Poly 400 - complete **LG 2**

for collecting and pumping out of sewage free of faeces, with shear key and pipe connection DN 110 suitable for KG, HT and KG 2000 pipes, **KRASO® Poly 400 - Pump** - (for sewage, excl. maintenance contract), empty pipe insert for the adjustment to subsequent floor construction
| DafStB waterproof concrete guideline: stress class 1 + 2

Type / Item	KRASO® Poly 400 / 80 - complete	KRASO® Poly 400 / 100 - complete
Internal diameter in cm	38.2	38.2
Internal height in cm	80	100
Intake DN 110 h1	30	30
Empty pipe DN 110 h2	34	54
Installation weight approx. in kg	21	23
KRASO® Pump Sump Poly 400 - complete - Cover: walkable	1,489 €	1,530 €
KRASO® Pump Sump Poly 400 - complete - Cover: water and odour-tight	1,682 €	1,717 €

We recommend the installation of an alarm system. The rubber seal is only used to secure the cover and not as a backflow seal!

Scope of supply: 1. Building shell element: **KRASO® Pump Sump Poly 400 - complete** with protective cover, pump sump protective cover for building shell, universal pump fastener

2. Installation set: **KRASO® Poly 400 - Pump** -, drain hose 1.25 m, internal diameter: 38 mm, universal hose connector 20 cm, empty pipe insert, **KRASO® Sealing Insert Poly** - complete -, **KRASO® Poly 400 Cover** - walkable -

Special sizes and designs available on request!