



The alternative
to a fixed-loose flange!



KRASO® Flange Pipes

Simple and effective integration into bituminous sealing

- + For new buildings and rehabilitation - according to DIN 18533 W1 -E and W2.1 -E
- + Simple and effective integration into bituminous sealing ("black tank"): bitumen thick coating and reactive sealing, sheeting, concrete and brick walls
- + Water pressure tight up to 1.5 bar - MPA-tested!
- + Made of dimensionally and pressure stable solid wall material with low abrasion! Installation even at lower temperatures
- + Pipe and pipe material in accordance with DIN EN 1401 (KG) or DIN EN 14758 (KG 2000)



KRASO® PU 50:
high-quality, permanently elastic and strong PU-sealant! (290 ml - cartridge).
Our recommendation for all products with **KRASO® Foil Flange!**



KRASO® Flange Pipe KG



KRASO® Flange Pipe for KG 2000



KRASO® Flange Pipe FE



KRASO® Type KMB



KRASO® Type KMB for KG 2000



KRASO® Type ÜSF



KRASO® Type KMB **LG1**

plug-in flange, for retrofit sealing of KG/HT pipes using **KRASO® Foil Flange** with bitumen thick coating and reactive sealings, with formed plug-in sleeve on one side and **KRASO® Foil Flange**, oil- and bitumen resistant, surrounding approx. 6 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DIN 18533 W1 -E and W2.1 -E

Item	KRASO® Type KMB			
Diameter DN	110	125	160	200
Plug-in length in cm	7	7.5	8	9
KRASO® Type KMB	49 €	52 €	63 €	80 €
KRASO® PU 50	22 €			

Further diameters available on request!



KRASO® Type KMB for KG 2000 **LG1**

plug-in flange, for retrofit sealing of KG 2000 pipes using **KRASO® Foil Flange** with bitumen thick coating and reactive sealings, with formed plug-in sleeve on one side and **KRASO® Foil Flange**, oil- and bitumen resistant, surrounding approx. 6 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DIN 18533 W1 -E and W2.1 -E

Item	KRASO® Type KMB for KG 2000			
Diameter DN	110	125	160	200
Plug-in length in cm	7	7.5	8	9
KRASO® Type KMB for KG 2000	60 €	70 €	85 €	122 €
KRASO® PU 50	22 €			

Further diameters available on request!



KRASO® Type ÜSF - slip-on flange **LG1**

for retrofit sealing of installed KG, HT or KG 2000 pipes, using **KRASO® Foil Flange** with bitumen sealing (e.g. KMB), with foil flange, oil- and bitumen resistant, surrounding approx. 15 cm. For the integration of the foil flange, we recommend our adhesive and sealant **KRASO® PU 50**. | DIN 18533 W1 -E and W2.1 -E

Item	KRASO® Type ÜSF					
Diameter DN	110	125	160	200	250	315
KRASO® Type ÜSF	87 €	95 €	113 €	208 €	307 €	411 €
KRASO® PU 50	22 €					

Further diameters available on request!



KRASO® PU 50 **LG1**

high-quality, permanently elastic and strong PU-sealant, also usable on moist surfaces, recommended for all products with **KRASO® Foil Flange**, colour black, 290 ml cartridge for cartridge presses

Item	PU sealant
KRASO® PU 50	22 €