



KRASO® Yard/Parking Level Drain

The high-performance drain
for e.g. underground car parks

- + **KRASO® Yard/Parking Level Drain** with 4.3 l/s drainage capacity according to DIN EN 1253
- + With frost proof odour barrier and removable sand trap basket
- + Load class A to 1.5 t or load class B up to 12.5 t
- + Connection either for KG, HT or KG 2000 pipes DN 110
- + With water pressure tight surrounding, thermally welded **KRASO® 4 Seal**: water pressure tight up to 10 bar!
- + DafStB waterproof concrete guideline: stress class 1 + 2, with flange DIN 18533 W1-E



KRASO® Yard/Parking Level Drain Type 1.5



KRASO® Yard/Parking Level Drain Type 1.5
with trowel flange with dovetail groove
(only for welding sheets, not for resin coating)



KRASO® Yard/Parking Level Drain Type 1.5
with stainless steel grate



KRASO® Yard/Parking Level Drain Type 1.5
with stainless steel grate with foil flange



KRASO® Yard/Parking Level Drain Type 12.5



KRASO® Yard/Parking Level Drain Type 12.5
with stainless steel grate

KRASO® Yard/Parking Level Drain **LG 1**

for the installation in areas with traffic

Type / Item	KRASO® Yard/Parking Level Drain Type 1.5	KRASO® Yard/Parking Level Drain Type 12.5
Drainage capacity	4.3 l/s	
Load class	load class A 15	load class B to 12.5 t
Base plate thickness	min. 20 cm	min. 15 or 20 cm
Connection	either for KG, HT or KG 2000 pipes DN 110	
KRASO® Yard/Parking Level Drain	282 €	511 €
KRASO® Yard/Parking Level Drain with trowel flange with dovetail groove	471 €	-
KRASO® Yard/Parking Level Drain with stainless steel grate	444 €	-
KRASO® Yard/Parking Level Drain with stainless steel grate with foil flange	632 €	-
KRASO® Yard/Parking Level Drain with stainless steel slot grate	-	708 €

Scope of supply: **KRASO® Yard/Parking Level Drain Type 1.5** with frost proof odour barrier, removable sand trap basket, with slot grate approx. 24 x 24 cm, cast iron, load class A to 1.5 t, vertical discharge • **KRASO® Yard/Parking Level Drain Type 12.5** with frost proof odour barrier, removable sand trap basket, with support frame made of eco-cast, 26 x 26 cm, with slot grate, load class B up to 12.5 t, vertical discharge